

Parking Lot Fixture

MFHID-PLL

Application

Parking areas, entrances, walkways, loading docks, or recreation areas.

Construction

Body: Sturdy die-cast aluminum housing and frame, with dark-bronze polyester powder-coat finish.

Lens: Tempered-glass lens, thermal-shock and impact resistant.

Reflector: Formed anodized aluminum reflector.

Ballast: Quad-tap CWA ballast.

Mounting: 2 3/8"-inch adjustable slip fitter.

Listing: UL Listed for wet location.

Electrical

UL listed wire rated for required temperature and voltage. Lamps is secured with Mogul Base.



Warranty

One year standard warranty on fixture. Ballast carries 3-5 year manufacture warranty.

Options

Sensors. (See available options)

Features

- Anodized aluminum reflector with high efficiency and wide beam spread.
- Quad-Tap 120 / 208 / 240 / 277v Ballast
- 400W Size: 16.5" square x 7" deep
- Factory supplied lamps are available in various CRI ratings, temperature colors and rated life
- Photo sensor compatible.

Ordering Information

Use the Flow chart below to configure the part number. Actual part number may vary due to configuration.

MFHID-PLL	Type Parking Lot Lighting Fixture
	Number of Lamps Req'd 250MH - 1-250w Pulse Start Metal Halide 320MH - 1-320w Pulse Start Metal Halide 400MH - 1-400w Pulse Start Metal Halide 350HPS - 1-250w High Pressure Sodium 400HPS - 1-400w High Pressure Sodium
	Options See Option Sheet
	Body Color Blank - Bronze